

Description

Fastener Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | AN123640 |
| Minimum Qty (MOQ): | 55 EA |
| NSN: | 5320-00-808-4967 |
| Schedule B: | 7508.90.5000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN123640 Specifications

| | |
|--|--|
| Fastener Length: | 0.552 Inches Minimum And 0.572 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.123 Inches Minimum And 0.126 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.210 Inches Minimum And 0.218 Inches Maximum |
| Grip Length: | 0.327 Inches Minimum And 0.347 Inches Maximum |
| Countersink Angle: | 98.5 Degrees Minimum And 101.5 Degrees Maximum |
| Material: | Nickel Alloy 600 Overall |
| Material Document And Classification: | Ams 7232 Assn Std Single Material Response Overall |

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123640> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.