

**Description**

Fastener Length: 7/16

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN123654
Minimum Qty (MOQ):	100
NSN:	5320-00-292-8442
Schedule B:	7508.90.5000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AN123654 Specifications

<b>Fastener Length:</b>	0.428 Inches Minimum And 0.448 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.154 Inches Minimum And 0.157 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.272 Inches Minimum And 0.280 Inches Maximum
<b>Grip Length:</b>	0.147 Inches Minimum And 0.167 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123654> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.