

**Description**

Fastener Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN123669
Minimum Qty (MOQ):	35 EA
NSN:	5320-01-504-6069
Schedule B:	7508.90.5000
ECCN:	EAR99



NO IMAGE  
AVAILABLE

## P/N AN123669 Specifications

<b>Fastener Length:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.189 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.337 Inches Minimum And 0.347 Inches Maximum
<b>End Item Identification:</b>	F119 Engine
<b>Grip Length:</b>	0.027 Inches Minimum And 0.047 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Rivet
<b>Material:</b>	Nickel Alloy 600 Overall
<b>Material Document And Classification:</b>	Ams 7232 Assn Std Single Material Response Overall

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123669> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.