

Description

Fastener Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN123669
Minimum Qty (MOQ):	35 EA
NSN:	5320-01-504-6069
Schedule B:	7508.90.5000
ECCN:	EAR99



* See page 2 for technical characteristics

P/N AN123669 Specifications

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.186 Inches Minimum And 0.189 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.337 Inches Minimum And 0.347 Inches Maximum
End Item Identification:	F119 Engine
Grip Length:	0.027 Inches Minimum And 0.047 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Rivet
Material:	Nickel Alloy 600 Overall
Material Document And Classification:	Ams 7232 Assn Std Single Material Response Overall

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123669> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.