

**Description**

Fastener Length: 35/64",

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN123672
Minimum Qty (MOQ):	20
NSN:	5320-00-270-2682
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AN123672 Specifications

<b>Fastener Length:</b>	0.552 Inches Minimum And 0.572 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.186 Inches Minimum And 0.189 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.337 Inches Minimum And 0.347 Inches Maximum
<b>Grip Length:</b>	0.214 Inches Minimum And 0.234 Inches Maximum
<b>Countersink Angle:</b>	98.5 Degrees Minimum And 101.5 Degrees Maximum
<b>Material:</b>	Nickel Alloy 600 Overall
<b>Material Document And Classification:</b>	Ams 7232 Assn Std Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN123672> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.