

## **P/N AN123686**

### **Description**

Fastener Length: 17/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN123686
Minimum Qty (MOQ):	100 EA
NSN:	5320-01-485-8022
Schedule B:	7508.90.5000
ECCN:	EAR99



<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN123686 Specifications**

Fastener Length:	0.521 Inches Minimum And 0.541 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.123 Inches Minimum And 0.126 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.210 Inches Minimum And 0.218 Inches Maximum
Grip Length:	0.296 Inches Minimum And 0.316 Inches Maximum
Countersink Angle:	98.5 Degrees Minimum And 101.5 Degrees Maximum
Material:	Nickel Alloy Overall
Material Document And Classification:	Ams 7232 Assn Std Single Material Response Overall

## **How to Order**

Order this rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/AN123686">https://military-fasteners.com/rivets/solid+rivets/AN123686</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.