

Description

Fastener Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN124952
Minimum Qty (MOQ):	1000 EA
NSN:	5320-00-545-7167
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N AN124952 Specifications

Fastener Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.061 Inches Minimum And 0.063 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.099 Inches Minimum And 0.107 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	Solution Heat Treated Overall
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 7228 Assn Std Single Material Response Overall

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN124952> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.