

Description

AN124973 Solid Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | AN124973 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-558-9377 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N AN124973 Specifications

| | |
|--|--|
| Fastener Length: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.093 Inches Minimum And 0.095 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.164 Inches Minimum And 0.172 Inches Maximum |
| Grip Length: | 0.196 Inches Minimum And 0.216 Inches Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams 7228 Assn Std Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN124973> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.