

Description

Fastener Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN124991
Minimum Qty (MOQ):	100
NSN:	5320-00-264-3219
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN124991 Specifications

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.123 Inches Minimum And 0.126 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.210 Inches Minimum And 0.218 Inches Maximum
Grip Length:	0.140 Inches Minimum And 0.160 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 7228 Assn Std Single Material Response Overall

How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN124991> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.