

**Description**

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN124995
Minimum Qty (MOQ):	170 EA
NSN:	5320-00-982-9941
Schedule B:	7508.90.5000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AN124995 Specifications

<b>Fastener Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.123 Inches Minimum And 0.126 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.210 Inches Minimum And 0.218 Inches Maximum
<b>Grip Length:</b>	0.390 Inches Minimum And 0.410 Inches Maximum
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Material Document And Classification:</b>	Ams 7228 Assn Std Single Material Response Overall

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN124995> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.