

Description

Fastener Length: 3/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---------------------------------------------|
| SKU / Model: | AN125420 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5320-00-279-1294 |
| Schedule B: | 7318.23.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN125420 Specifications

| | |
|----------------------------------------------|----------------------------------------------------|
| Fastener Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Head Style: | Universal |
| Head Height: | 0.040 Inches Minimum And 0.050 Inches Maximum |
| Shank Diameter: | 0.093 Inches Minimum And 0.095 Inches Maximum |
| Shank Style: | Straight |
| Head Major Diameter: | 0.179 Inches Minimum And 0.197 Inches Maximum |
| Grip Length: | 0.009 Inches Minimum And 0.029 Inches Maximum |
| Material: | Steel Comp 347 Overall |
| Material Document And Classification: | Ams 7229 Assn Std Single Material Response Overall |

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN125420> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.