

## **P/N AN125440**

### **Description**

Fastener Length: 19/64"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN125440

Minimum Qty (MOQ): 80 EA

NSN: 5320-00-985-3789

Schedule B: 7318.23.0000

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN125440 Specifications

Fastener Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.123 Inches Minimum And 0.126 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.077 Inches Minimum And 0.097 Inches Maximum
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 7228 Assn Std Single Material Response Overall

## **How to Order**

Order this rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/solid+rivets/AN125440">https://military-fasteners.com/rivets/solid+rivets/AN125440</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.