

Description

Fastener Length: 3/8", roughly 550 pieces per pound

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN125441
Minimum Qty (MOQ):	1 Pound
NSN:	5320-00-994-7079
Schedule B:	7318.23.0000
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N AN125441 Specifications

Fastener Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Style:	Universal
Head Height:	0.054 Inches Minimum And 0.064 Inches Maximum
Shank Diameter:	0.124 Inches Minimum And 0.128 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.238 Inches Minimum And 0.262 Inches Maximum
Grip Length:	0.177 Inches Minimum And 0.197 Inches Maximum
Shear Strength:	25000 Single Pounds Per Square Inch
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 303f Overall Or Steel Comp 303s Overall Or Steel Comp 303se Overall Or Steel Comp 304 Overall Or Steel Comp 304l Overall Or Steel Comp 305 Overall Or Steel Comp 308 Overall Or Steel Comp 309 Overall Or Steel Comp 309s Overall Or Steel Comp 310 Overall Or Steel Comp 310s Overall Or Steel Comp 314 Overall Or Steel Comp 316 Overall Or Steel Comp 316l Overall Or Steel Comp 317 Overall Or Steel Comp 321 Overall Or Steel Comp 323 Overall Or Steel Comp 324 Overall Or Steel Comp 347 Overall Or Steel Comp 348 Overall Or Steel Comp 385 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall And Qq-p-35 Fed Spec 1st Treatment Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN125441> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.