

**Description**

Fastener Length: 35/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN125630
Minimum Qty (MOQ):	1000 EA
NSN:	5320-00-999-9322
Schedule B:	7318.23.0000
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N AN125630 Specifications

<b>Fastener Length:</b>	0.562 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.080 Inches Minimum And 0.090 Inches Maximum
<b>Shank Diameter:</b>	0.182 Inches Minimum And 0.192 Inches Maximum
<b>Shank Style:</b>	Straight
<b>Head Major Diameter:</b>	0.356 Inches Minimum And 0.394 Inches Maximum
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Ams 7225 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2400 Assn Std Single Treatment Response Overall

## How to Order

Order this rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/AN125630> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.