

# **P/N AN125989**

## **Description**

AN125989 Plain Stud

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN125989
Minimum Qty (MOQ):	10
NSN:	5307-00-264-2427
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N AN125989 Specifications**

Thread Class:	3a Nut Thread
Thread Pitch Diameters:	+0.2248/+0.2263 Inches Stud Thread
Thread Direction:	Right-hand Nut Thread
Thread Direction:	Right-hand Stud Thread
Thread Length:	0.500 Inches Minimum Nut Thread
Thread Length:	0.688 Inches Minimum Stud Thread
Overall Length:	1.312 Inches Nominal
Thread Quantity Per Inch:	20 Stud Thread
Thread Quantity Per Inch:	28 Nut Thread
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	0.250 Inches Nut Thread
Nominal Thread Size:	0.250 Inches Stud Thread
Special Features:	0.221 To 0.231 In. Dia Of Unthreaded Portion
Material:	Steel Comp 8740
Material Document And Classification:	Ams 6322 Assn Std Single Material Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf Nut Thread
Thread Series Designator:	Uns Stud Thread

### **How to Order**

Order this plain stud from our inventory online by visiting <a href="https://military-fasteners.com/studs/plain+studs/AN125989">https://military-fasteners.com/studs/plain+studs/AN125989</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.