

Description

AN126006 Plain Stud

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | AN126006 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5307-00-264-2422 |
| Schedule B: | 7318.15.5030 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN126006 Specifications

| | |
|---|---|
| Thread Class: | 3a Nut Thread |
| Thread Pitch Diameters: | +0.2218/+0.2233 Inches Stud Thread |
| Thread Direction: | Right-hand Nut Thread |
| Thread Direction: | Right-hand Stud Thread |
| Thread Length: | 0.552 Inches Minimum Nut Thread And 0.572 Inches Maximum Nut Thread |
| Thread Length: | 0.678 Inches Minimum Stud Thread And 0.698 Inches Maximum Stud Thread |
| Overall Length: | 1.490 Inches Minimum And 1.510 Inches Maximum |
| Thread Quantity Per Inch: | 20 Stud Thread |
| Thread Quantity Per Inch: | 28 Nut Thread |
| Hardness Rating: | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.250 Inches Nut Thread |
| Nominal Thread Size: | 0.250 Inches Stud Thread |
| Surface Finish: | 63.0 Microinches Shank |
| Material: | Steel Comp 8740 |
| Material Document And Classification: | Ams 6322 Assn Std Single Material Response |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Ams 2400 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unf Nut Thread |
| Thread Series Designator: | Uns Stud Thread |

How to Order

Order this plain stud from our inventory online by visiting <https://military-fasteners.com/studs/plain+studs/AN126006> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.