

Description

AN126006 Plain Stud

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN126006
Minimum Qty (MOQ):	10
NSN:	5307-00-264-2422
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN126006 Specifications

Thread Class:	3a Nut Thread
Thread Pitch Diameters:	+0.2218/+0.2233 Inches Stud Thread
Thread Direction:	Right-hand Nut Thread
Thread Direction:	Right-hand Stud Thread
Thread Length:	0.552 Inches Minimum Nut Thread And 0.572 Inches Maximum Nut Thread
Thread Length:	0.678 Inches Minimum Stud Thread And 0.698 Inches Maximum Stud Thread
Overall Length:	1.490 Inches Minimum And 1.510 Inches Maximum
Thread Quantity Per Inch:	20 Stud Thread
Thread Quantity Per Inch:	28 Nut Thread
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	0.250 Inches Nut Thread
Nominal Thread Size:	0.250 Inches Stud Thread
Surface Finish:	63.0 Microinches Shank
Material:	Steel Comp 8740
Material Document And Classification:	Ams 6322 Assn Std Single Material Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf Nut Thread
Thread Series Designator:	Uns Stud Thread

How to Order

Order this plain stud from our inventory online by visiting <https://military-fasteners.com/studs/plain+studs/AN126006> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.