

P/N AN126118

Description

Thread Size: 1/4", Length: 2-5/8", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: AN126118

Minimum Qty (MOQ): 40 EA

NSN: 5307-00-637-7231

Schedule B: 7318.15.5030

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN126118 Specifications

Thread Class:	3a Nut Thread
Thread Pitch Diameters:	+0.2338/+0.2353 Inches Stud Thread
Thread Direction:	Right-hand Nut Thread
Thread Direction:	Right-hand Stud Thread
Thread Length:	0.562 Inches Minimum Nut Thread
Thread Length:	0.688 Inches Minimum Stud Thread
Overall Length:	2.310 Inches Minimum And 2.990 Inches Maximum
Thread Quantity Per Inch:	20 Stud Thread
Thread Quantity Per Inch:	28 Nut Thread
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	0.250 Inches Nut Thread
Nominal Thread Size:	0.250 Inches Stud Thread
Surface Finish:	63.0 Microinches Shank
Material:	Steel Comp 8740
Material Document And Classification:	Ams 6322 Assn Std Single Material Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unc Stud Thread
Thread Series Designator:	Unf Nut Thread

How to Order

Order this stud from our inventory online by visiting https://military-fasteners.com/gaskets/gaskets/gaskets/AN126118 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/gaskets/gaskets/gaskets/AN126118 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/gaskets/gaskets/AN126118 and selecting the quantity you want then click "add to cart".