

## P/N AN126324

### **Description**

Thread Size: 1/4", Length: 1-5/8", Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN126324

Minimum Qty (MOQ): 10 EA

NSN: 5307-00-292-5857

Schedule B: 7318.15.5030

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN126324 Specifications

Thread Class:	3a Nut Thread
Thread Pitch Diameters:	+0.2810/+0.2825 Inches Stud Thread
Thread Direction:	Right-hand Nut Thread
Thread Direction:	Right-hand Stud Thread
Thread Length:	0.615 Inches Minimum Nut Thread And 0.635 Inches Maximum Nut Thread
Thread Length:	0.834 Inches Minimum Stud Thread And 0.854 Inches Maximum Stud Thread
Overall Length:	1.615 Inches Minimum And 1.635 Inches Maximum
Thread Quantity Per Inch:	18 Stud Thread
Thread Quantity Per Inch:	24 Nut Thread
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	0.312 Inches Nut Thread
Nominal Thread Size:	0.312 Inches Stud Thread
Surface Finish:	63.0 Microinches Shank
Material:	Steel Comp 8740
Material Document And Classification:	Ams 6322 Assn Std Single Material Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unc Stud Thread
Thread Series Designator:	Unf Nut Thread

## **How to Order**

Order this stud from our inventory online by visiting <a href="https://military-fasteners.com/gaskets/gaskets/AN126324">https://military-fasteners.com/gaskets/gaskets/gaskets/AN126324</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.