

P/N AN126409

Description

Thread Size: 1/4", Length: 2-5/8", Thread Length: 5/8"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: AN126409

Minimum Qty (MOQ): 5 EA

NSN: 5307-00-254-9650

Schedule B: 7318.15.5030

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN126409 Specifications

Thread Class:	3a Nut Thread
Thread Pitch Diameters:	+0.2840/+0.2855 Inches Stud Thread
Thread Direction:	Right-hand Nut Thread
Thread Direction:	Right-hand Stud Thread
Thread Length:	0.625 Inches Minimum Nut Thread
Thread Length:	0.844 Inches Minimum Stud Thread
Overall Length:	2.615 Inches Minimum And 2.635 Inches Maximum
Thread Quantity Per Inch:	18 Stud Thread
Thread Quantity Per Inch:	24 Nut Thread
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	0.312 Inches Nut Thread
Nominal Thread Size:	0.312 Inches Stud Thread
Surface Finish:	63.0 Microinches Shank
Material:	Steel Comp 8740
Material Document And Classification:	Ams 6322 Assn Std Single Material Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf Nut Thread
Thread Series Designator:	Uns Stud Thread

How to Order

Order this stud from our inventory online by visiting https://military-fasteners.com/gaskets/gaskets/AN126409 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/gaskets/gaskets/AN126409 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/gaskets/gaskets/AN126409 and selecting the quantity you want then click "add to cart".