

Description

Thread Size: 1/4", Length: 4-1/2", Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN126502
Minimum Qty (MOQ):	1 EA
NSN:	5307-01-047-8041
Schedule B:	7318.15.5051
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN126502 Specifications

Thread Class:	3a Nut Thread
Thread Pitch Diameters:	+0.2930/+0.2945 Inches Stud Thread
Thread Direction:	Right-hand Nut Thread
Thread Direction:	Right-hand Stud Thread
Thread Length:	0.625 Inches Minimum Nut Thread And 0.708 Inches Maximum Nut Thread
Thread Length:	0.844 Inches Minimum Stud Thread And 0.955 Inches Maximum Stud Thread
Overall Length:	4.490 Inches Minimum And 4.510 Inches Maximum
Thread Quantity Per Inch:	18 Stud Thread
Thread Quantity Per Inch:	24 Nut Thread
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	0.312 Inches Nut Thread
Nominal Thread Size:	0.312 Inches Stud Thread
Surface Finish:	32.0 Microinches Nut Thd
Surface Finish:	32.0 Microinches Stud Thd
Surface Finish:	63.0 Microinches Shank
lii Part Name Assigned By Controlling Agency:	Stud,plain
Material:	Steel Comp 8740
Material Document And Classification:	Ams 6322 Assn Std Single Material Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf Nut Thread
Thread Series Designator:	Uns Stud Thread

How to Order

Order this stud from our inventory online by visiting <https://military-fasteners.com/gaskets/gaskets/AN126502> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.