

**Description**

Thread Size: 1/4", Length: 1-3/4", Thread Length: 7/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN126546
Minimum Qty (MOQ):	5
NSN:	5307-00-079-7203
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN126546 Specifications

<b>Thread Class:</b>	3a Nut Thread
<b>Thread Pitch Diameters:</b>	+0.2810/+0.2825 Inches Stud Thread
<b>Thread Pitch Diameters:</b>	+0.2810 To 0.2825 Inches Stud Thread
<b>Thread Direction:</b>	Right-hand Nut Thread
<b>Thread Direction:</b>	Right-hand Stud Thread
<b>Thread Length:</b>	0.719 Inches Minimum Nut Thread
<b>Thread Length:</b>	0.844 Inches Minimum Stud Thread
<b>Overall Length:</b>	1.678 Inches Minimum And 1.698 Inches Maximum
<b>Thread Quantity Per Inch:</b>	18 Stud Thread
<b>Thread Quantity Per Inch:</b>	24 Nut Thread
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Nominal Thread Size:</b>	0.312 Inches Nut Thread
<b>Nominal Thread Size:</b>	0.312 Inches Stud Thread
<b>Surface Finish:</b>	32.0 Microinches Nut Thd
<b>Surface Finish:</b>	32.0 Microinches Stud Thd
<b>Surface Finish:</b>	63.0 Microinches Shank
<b>Material:</b>	Steel Comp 8740
<b>Material Document And Classification:</b>	Ams 6322 Assn Std Single Material Response
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2400 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf Nut Thread
<b>Thread Series Designator:</b>	Uns Stud Thread

## How to Order

Order this plain stud from our inventory online by visiting <https://military-fasteners.com/studs/plain+studs/AN126546> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.