

Description

Thread Size: 3/8", Length: 1-11/16", Thread Length: 15/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN126618
Minimum Qty (MOQ):	5 EA
NSN:	5307-00-068-0421
Schedule B:	7318.15.5030
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN126618 Specifications

Thread Class:	2a Stud Thread
Thread Class:	3a Nut Thread
Thread Pitch Diameters:	+0.3392/+0.3407 Inches Stud Thread
Thread Pitch Diameters:	+0.3392 To 0.3407 Inches Stud Thread
Thread Direction:	Right-hand Nut Thread
Thread Direction:	Right-hand Stud Thread
Thread Length:	0.625 Inches Minimum Nut Thread
Thread Length:	0.938 Inches Minimum Stud Thread
Overall Length:	1.688 Inches Nominal
Thread Quantity Per Inch:	16 Nut Thread
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	0.375 Inches Nut Thread
Surface Finish:	32.0 Microinches Nut Thd
Surface Finish:	32.0 Microinches Stud Thd
Surface Finish:	63.0 Microinches Shank
Material:	Steel Comp 8740
Material Document And Classification:	Ams 6322 Assn Std Single Material Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unc Nut Thread

How to Order

Order this stud from our inventory online by visiting <https://military-fasteners.com/gaskets/gaskets/AN126618> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.