

Description

Thread Size: 3/8", Length: 2-1/8", Thread Length: 1

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN126952
Minimum Qty (MOQ):	1
NSN:	5307-00-546-5002
Schedule B:	7318.15.5051
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN126952 Specifications

Thread Class:	3a Nut Thread
Thread Pitch Diameters:	+0.3512/+0.3527 Inches Stud Thread
Thread Direction:	Right-hand Nut Thread
Thread Direction:	Right-hand Stud Thread
Thread Length:	0.928 Inches Minimum Stud Thread And 0.948 Inches Maximum Stud Thread
Thread Length:	0.678 Inches Minimum Nut Thread And 0.698 Inches Maximum Nut Thread
Overall Length:	2.115 Inches Minimum And 2.135 Inches Maximum
Thread Quantity Per Inch:	16 Stud Thread
Thread Quantity Per Inch:	24 Nut Thread
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	0.375 Inches Nut Thread
Nominal Thread Size:	0.375 Inches Stud Thread
Surface Finish:	63.0 Microinches Shank
Material:	Steel Comp 8740
Material Document And Classification:	Ams 6322 Assn Std Single Material Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf Nut Thread
Thread Series Designator:	Uns Stud Thread

How to Order

Order this plain stud from our inventory online by visiting <https://military-fasteners.com/studs/plain+studs/AN126952> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.