

Description

Thread Size: 1/4", Length: 1-3/4", Thread Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN128743
Minimum Qty (MOQ):	5
NSN:	5307-01-199-9508
Schedule B:	7318.15.5030
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N AN128743 Specifications

Thread Class:	3a Nut Thread
Thread Pitch Diameters:	+0.2840/+0.2855 Inches Stud Thread
Thread Direction:	Right-hand Nut Thread
Thread Direction:	Right-hand Stud Thread
Thread Length:	0.625 Inches Minimum Nut Thread
Thread Length:	0.844 Inches Minimum Stud Thread
Overall Length:	1.678 Inches Minimum And 1.698 Inches Maximum
Distance From Cotter Pin Hole Centerline To Nut End:	0.110 Inches Nominal First Hole
Cotter Pin Hole Diameter:	0.065 Inches Minimum First Hole And 0.072 Inches Maximum First Hole
Thread Quantity Per Inch:	18 Stud Thread
Thread Quantity Per Inch:	24 Nut Thread
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Nominal Thread Size:	0.312 Inches Nut Thread
Nominal Thread Size:	0.312 Inches Stud Thread
Surface Finish:	32.0 Microinches Nut Thd
Surface Finish:	32.0 Microinches Stud Thd
Surface Finish:	63.0 Microinches Shank
Material:	Steel Comp 8740
Material Document And Classification:	Ams6322 Assn Std Single Material Response
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf Nut Thread
Thread Series Designator:	Uns Stud Thread

How to Order

Order this plain stud from our inventory online by visiting <https://military-fasteners.com/studs/plain+studs/AN128743> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.