

**Description**

Fastener Length: 9/16", Hole Diameter: 1/16", Thread: 1/4-28, Head Width: 7/32", Thread Length: 9/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN148657                                  |
| Minimum Qty (MOQ):      | 15 EA                                     |
| NSN:                    | 5305-00-286-0013                          |
| Schedule B:             | 7318.15.2010                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N AN148657 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.501 Inches Minimum And 0.572 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 0.552 Inches Minimum And 0.572 Inches Maximum                       |
| <b>Head Style:</b>                                    | Flat Chamfer  |
| <b>Head Diameter:</b>                                 | 0.428 Inches Minimum And 0.448 Inches Maximum                       |
| <b>Head Height:</b>                                   | 0.250 Inches Minimum And 0.270 Inches Maximum                       |
| <b>Hole Diameter:</b>                                 | 0.070 Inches Nominal  |
| <b>Internal Drive Style:</b>                          | Hexagon   |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches  |
| <b>Width Across Flats:</b>                            | 0.219 Inches Minimum And 0.221 Inches Maximum                       |
| <b>Hole Quantity:</b>                                 | 6   |
| <b>Hole Type:</b>                                     | Drilled   |
| <b>Thread Quantity Per Inch:</b>                      | 28  |
| <b>Hardness Rating:</b>                               | 32.0 Rockwell C Minimum Overall And 36.0 Rockwell C Maximum Overall |
| <b>Hole Configuration Style:</b>                      | Round   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads  |
| <b>Surface Finish:</b>                                | 63.0 Microinches Bearing Surface Of Head                            |
| <b>Material:</b>                                      | Steel Comp 8740 Overall   |
| <b>Material Document And Classification:</b>          | Ams 6322 Assn Std Single Material Response Overall                  |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Ams 2400 Assn Std Single Treatment Response Overall                 |
| <b>Thread Series Designator:</b>                      | Unf   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN148657> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.