



Military-Fasteners.com

P/N AN148657

Description

Fastener Length: 9/16", Hole Diameter: 1/16", Thread: 1/4-28, Head Width: 7/32", Thread Length: 9/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN148657
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-286-0013
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N AN148657 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.501 Inches Minimum And 0.572 Inches Maximum
<b>Fastener Length:</b>	0.552 Inches Minimum And 0.572 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.428 Inches Minimum And 0.448 Inches Maximum
<b>Head Height:</b>	0.250 Inches Minimum And 0.270 Inches Maximum
<b>Hole Diameter:</b>	0.070 Inches Nominal
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Width Across Flats:</b>	0.219 Inches Minimum And 0.221 Inches Maximum
<b>Hole Quantity:</b>	6
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	28
<b>Hardness Rating:</b>	32.0 Rockwell C Minimum Overall And 36.0 Rockwell C Maximum Overall
<b>Hole Configuration Style:</b>	Round
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Surface Finish:</b>	63.0 Microinches Bearing Surface Of Head
<b>Material:</b>	Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Ams 6322 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2400 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/AN148657> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.