

P/N AN148674

Description

Fastener Length: 1-5/8", Hole Diameter: 5/64", Thread: 1/4-28, Head Width: 7/32", Thread Length: 43/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN148674
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-551-0064
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN148674 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.669 Inches Minimum And 0.820 Inches Maximum
Fastener Length:	1.615 Inches Minimum And 1.635 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Height:	0.250 Inches Minimum And 0.270 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.250 Inches
Width Across Flats:	0.219 Inches Minimum And 0.221 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hardness Rating:	32.0 Rockwell C Minimum Overall And 36.0 Rockwell C Maximum Overall
Hole Configuration Style:	Round Longitudinal Hole
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf
Tillead Series Designator.	OIII

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN148674 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.