

Description

Fastener Length: 1-1/16", Hole Diameter: 1/16", Thread: 3/8-24, Head Width: 5/16", Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN148865
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-273-6230
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN148865 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.989 Inches Minimum And 1.072 Inches Maximum
Fastener Length:	1.052 Inches Minimum And 1.072 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.552 Inches Minimum And 0.572 Inches Maximum
Head Height:	0.360 Inches Minimum And 0.380 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.313 Inches Minimum And 0.316 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Hardness Rating:	32.0 Rockwell C Minimum And 36.0 Rockwell C Maximum Overall
Hole Configuration Style:	Round Internal Hexagon
Criticality Code Justification:	Feat
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Special Features:	Part Has Critical Tolerance On The Diameter Of The Item As Well As Application
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN148865> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.