

Description

Fastener Length: 2-31/32", Thread: 7/8-14, Thread Length: 1-1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN14C26A
Minimum Qty (MOQ):	1
NSN:	5306-01-371-1704
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN14C26A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Nominal
Fastener Length:	2.922 Inches Minimum And 2.969 Inches Maximum
Head Style:	Hexagon
Head Height:	0.453 Inches Minimum And 0.485 Inches Maximum
Width Between Flats:	1.240 Inches Minimum And 1.253 Inches Maximum
Nominal Thread Diameter:	0.875 Inches
Thread Quantity Per Inch:	14
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Surface Finish:	63.0 Microinches Grip
Material:	Steel Comp 431 Overall
Material Document And Classification:	Mil-s-18732 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-b-6812 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	88044-an-14 Government Specification

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN14C26A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.