

P/N AN173-32

Military-Fasteners.com

Description

Fastener Length: 3-5/16", Thread: 10-32, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AN17332
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-180-1730
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN173-32 Specifications

Thread Class:3aThread Direction:Right-handThread Length:0.375 Inches Minimum And 0.453 Inches MaximumFastener Length:0.366 Inches Minimum And 0.312 Inches MaximumHead Style:HexagonHead Height:0.109 Inches Minimum And 0.317 Inches MaximumWidth Between Flats:0.365 Inches Minimum And 0.377 Inches MaximumOrip Diameter:0.1089 Inches Minimum And 0.1971 Inches MaximumShank Unthreaded Hole Diameter:0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleNomial Thread Diameter:0.190 Inches Minimum And 2.891 Inches MaximumOrip Length:0.265 Inches Minimum And 2.891 Inches MaximumThread Quantity Per Inch:32Batterial Estrength:2.500 Pounds Per Square InchMinimum Tensile Strength:2.500 Pounds Per Square InchBatterial Estrength:2.500 Pounds Per Square InchMarcel To Shank Hole2.51 Inches Minimum First Hole And 3.156 Inches Maximum OverallPread Carest2.52 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial Resonase Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial Resonase Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6038 Mil Spec 3th Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6038 Mil Spe		
Thread Length:0.375 Inches Minimum And 0.453 Inches MaximumFastener Length:3.266 Inches Minimum And 3.312 Inches MaximumHead Style:HexagonHead Height:0.109 Inches Minimum And 0.141 Inches MaximumOligo Inches Minimum And 0.377 Inches MaximumGrip Diameter:0.365 Inches Minimum And 0.1894 Inches MaximumOnthes Minimum And 0.1894 Inches MaximumShank Unthreaded Hole Diameter:0.109 Inches Minimum First Hole And 0.080 Inches Maximum First HoleNomial Thread Diameter:0.109 Inches Minimum And 2.891 Inches MaximumOrip Length:2.859 Inches Minimum And 2.891 Inches MaximumThread Quantity Per Inch:2.5000 Pounds Per Square InchHardness Rating:0.60. Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface Tros Mark Hole3.125 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial:See Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Mil-s-6039 Mil Spec 2nd Material Response Overall Or Mi	Thread Class:	За
Fastener Length:32.66 Inches Minimum And 3.312 Inches MaximumHead Style:HexagonHead Height:0.109 Inches Minimum And 0.141 Inches MaximumWidth Between Flats:0.365 Inches Minimum And 0.377 Inches MaximumOrip Diameter:0.1889 Inches Minimum And 0.1894 Inches MaximumShark Unthreaded Hole Diameter:0.190 Inches Minimum First Hole And 0.080 Inches Maximum First HoleNominal Thread Diameter:0.190 Inches Minimum And 2.891 Inches MaximumOrip Length:2.859 Inches Minimum And 2.891 Inches MaximumThread Quantity Per Inch:32Bistnee From Head Largest2.600 Pounds Per Square InchBistnee From Head Largest2.150 Inches Minimum First Hole And 3.150 Inches Maximum OverallMaterial2.150 Inches Minimum First Hole And 3.150 Inches Maximum First HoleMaterial Strength:1.250 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial Comp Athal Comp Athal Overall Or Steel Comp B740 Overall Or Steel Comp B730 Overall Or Steel Comp Athal Overall Or Steel Comp Athal Overall Or Steel Comp Athal Stee Stee Athal Athal Stee Athal Athal Stee Athal Stee Athal Stee Athal Stee Athal Stee Athal Stee Athal Athal Stee Athal Athal Stee Athal Stee Athal Stee Athal Stee Athal Athal Stee Athal Athal Stee AthAlterial Response Overall Or Mil-s-6058 Mil Spee Ath Material R	Thread Direction:	Right-hand
Head Style:HexagonHead Height:0.109 Inches Minimum And 0.141 Inches MaximumWidth Between Flats:0.365 Inches Minimum And 0.377 Inches MaximumGrip Dameter:0.1889 Inches Minimum And 0.1894 Inches MaximumShank Unthreadel Hole Datemete:0.070 Inches Minimum And 0.0800 Inches Maximum First HoleShank Unthread Diameter:0.109 Inches Minimum And 0.2891 Inches Maximum First HoleSominal Thread Diameter:0.190 Inches Minimum And 2.891 Inches Maximum First HoleGrip Length:2.859 Inches Minimum And 2.891 Inches MaximumThread Quantity Per Inch:32Bistance From Head Largest Bearing Surface To Shank Hole2.500 Pounds Per Square InchBistance From Head Largest Bearing Surface To Shank Hole3.125 Inches Minimum First Hole And 3.156 Inches Maximum First Hole Coverall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8730 Overall Or Steel Comp 4037 OverallMaterial:Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Milis-s626 Mil Spec 1st Material Response Overall Or Milis-s6049 Mil Spec 2nd Material Response Overall Or Milis-s6050 Mil Spec 3rd Maxerial Response Overall Or Milis-s6049 Mil Spec 2nd Material Response Overall Or Milis-s6050 Mil Spec 3rd Maxerial Response Overall Or Milis-s6049 Mil Spec 2nd Material Response Overall Or Milis-s6050 Mil Spec 3rd Maxerial Response Overall Or Milis-s6049 Mil Spec 2nd Material Response Overall Or Milis-s6050 Mil Spec 3rd Maxerial Response Overall Or Milis-s6049 Mil Spec 3rd Maxerial Response Overall Or Milis-s6049 Milis Spec 3rd Maxerial Response Overall Or Milis-s6049 Milis Spec 3rd Maxerial Response Overall Or Milis-s6049 Milis Spec 3rd Maxerial Response Overall Or Milis	Thread Length:	0.375 Inches Minimum And 0.453 Inches Maximum
Head Height:0.109 Inches Minimum And 0.141 Inches MaximumWidth Between Flats:0.365 Inches Minimum And 0.377 Inches MaximumGrip Diameter:0.1889 Inches Minimum And 0.1894 Inches MaximumShank Unthreaded Hole Diameter:0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleNoninal Thread Diameter:0.070 Inches Minimum And 2.891 Inches Maximum First HoleOrig Length:2.859 Inches Minimum And 2.891 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole3.25 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-6526 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6059 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6059 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6059 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6059 Mil Spec 3rd Material Response Overall Or Mil-s-6059 Mil Spec 2nd Material Response Overall Or Mil-s-6059 Mil	Fastener Length:	3.266 Inches Minimum And 3.312 Inches Maximum
Width Between Flats:0.365 Inches Minimum And 0.377 Inches MaximumGrip Diameter:0.1889 Inches Minimum And 0.1894 Inches Maximum First HoleShank Unthreaded Hole Diameter:0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleNominal Thread Diameter:0.190 InchesOng Length:2.859 Inches Minimum And 2.891 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole3.125 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial Document And Classification:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Mil-s-6050 Mil Spec 3th Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6059 Mil Spec 4th Material Response Overall Or Mil-s-6058 Mil Spec 3th Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6058 Mil Spec 3th Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6058 Mil Spec 3th Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6058 Mil Spec 3th Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6058 Mil Spec 3th Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6058 Mil Spec 3th Material Response Overall Or Mil-s-6058 Mil Spec 3th Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6058 Mil Spec 3th Material Response Overall Or Mil-s-6058 Mil Spec 3th Material Response Overall Or Mil-s-6058 Mil Spec 3th Material Response Overall Or Mil-	Head Style:	Hexagon
Grip Diameter:0.1889 Inches Minimum And 0.1894 Inches MaximumShak Unthreaded Hole Diameter:0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleNominal Thread Diameter:0.190 InchesGrip Length:2.859 Inches Minimum And 2.891 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole3.125 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mili-s-5626 Mil Spec 1 st Material Response Overall Or Mil-s-6049 Mil Spec 2 nd Material Response Overall Or Mil-s-6050 Mil Spec 3 rd Material Response Overall Or Mil-s-6098 Mil Spec 4 Material Response Overall Or Mil-s-6758 Mil Spec 5 th Material Response OverallSurface Treatment:Cadmium Overall Pape Sciel St Material Response OverallSurface Treatment Document And Classification:Qep-416.type 2,class 3 Fed Spec Single Treatment Response Overall	Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Shank Unthreaded Hole Diameter:0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleNominal Thread Diameter:0.190 InchesGrip Length:2.859 Inches Minimum And 2.891 Inches MaximumThread Quantity Per Inch:3Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:3.125 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial:Seel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 OverallMaterial:Steel Comp 4100 Verall Or Steel Comp 4037 OverallSurface Treatment:Cadmium OverallSurface Tre	Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Nominal Thread Diameter:0.190 InchesGrip Length:2.859 Inches Minimum And 2.891 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.00 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole3.125 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Milis-s626 Mil Spec 1st Material Response Overall Or Milis-6098 Mil Spec 4th Material Response Overall Or Milis-6758 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Quep-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Grip Diameter:	0.1889 Inches Minimum And 0.1894 Inches Maximum
Grip Length:2.859 Inches Minimum And 2.891 Inches MaximumGrip Length:2.859 Inches Minimum And 2.891 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole3.125 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Miterial Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Miterial Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Miterial Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Miterial Response Overall Or Mil-s-6098 Diverall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Miterial Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Miterial Response Overall Or Mil-s-6098 Sil Spec Single Treatment Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6058 Mil Spec 5th Material Response Overall Or Mil-s-6058 Mil Spec 5th Material Response Overall Or	Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Thread Quantity Per Inch:32Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole center:3.125 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial Document And Classification:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 overall Or Steel Comp 4037 OverallSurface Treatment:Cadmium Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response OverallSurface Treatment Document And Classification:Q-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.190 Inches
Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:3.125 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 OverallMaterial:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium OverallOurp-416,type 2,class 3 Fed Spec Single Treatment Response OverallOverall	Grip Length:	2.859 Inches Minimum And 2.891 Inches Maximum
Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:3.125 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Overall Or Steel Comp 4037 OverallSurface Treatment:Cadmium OverallOq-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallOverall	Thread Quantity Per Inch:	32
Distance From Head Largest Bearing Surface To Shank Hole3.125 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Bearing Surface To Shank Hole Center:3.125 Inches Minimum First Hole And 3.156 Inches Maximum First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment And Classification:Qu-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams,6300 Assn Std 6th Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Bearing Surface To Shank Hole	3.125 Inches Minimum First Hole And 3.156 Inches Maximum First Hole
Material Document And Classification:Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams,6300 Assn Std 6th Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Material:	
Surface Treatment Document And Classification:		Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or
Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall	Surface Treatment:	Cadmium Overall
Thread Series Designator: Unf		Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/AN173-32</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.