

**Description**

length: 17/32", grip: 1/8", thread: 10-32, cadmium plated steel, undrilled shank, AN173 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN1734A
Minimum Qty (MOQ):	50
NSN:	5306-00-180-3342
Schedule B:	7318.15.2095
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N AN173-4A Specifications

<b>Thread Class:</b>	3a
<b>Thread Length:</b>	0.406 Inches Minimum
<b>Fastener Length:</b>	0.531 Inches Nominal
<b>Head Height:</b>	0.109 Inches Minimum And 0.141 Inches Maximum
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
<b>Material Document And Classification:</b>	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN173-4A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.