

P/N AN173-4A

Description

length: 17/32", grip: 1/8", thread: 10-32, cadmium plated steel, undrilled shank, AN173 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN1734A

Minimum Qty (MOQ): 50

NSN: 5306-00-180-3342

Schedule B: 7318.15.2095

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)











^{*} See page 2 for technical characteristics

P/N AN173-4A Specifications

Thread Class:	3a
Thread Length:	0.406 Inches Minimum
Fastener Length:	0.531 Inches Nominal
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Material:	Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/AN173-4A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.