

Description

Fastener Length: 3/4", Thread: 10-32, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN173C6 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-282-0914 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN173C6 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.406 Inches Minimum |
| Fastener Length: | 0.781 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.109 Inches Minimum And 0.141 Inches Maximum |
| Width Between Flats: | 0.365 Inches Minimum And 0.377 Inches Maximum |
| Grip Diameter: | 0.1889 Inches Minimum And 0.1894 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.070 Inches Nominal First Hole |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.375 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.641 Inches Nominal First Hole |
| Surface Finish: | 63.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 63.0 Microinches Grip |
| Material: | Steel Comp 431 Overall |
| Material Document And Classification: | Mil-s-18732 Mil Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unf |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN173C6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.