

P/N AN173C7A

Military-Fasteners.com

Description

Fastener Length: 15/16", Thread: 10-32, Thread Length: 29/64",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AN173C7A
Minimum Qty (MOQ):	20
NSN:	5306-00-584-7523
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN173C7A Specifications

ad Class: 3a	
ad Direction: Right-hand	
ad Length: 0.374 Inch	es Minimum And 0.453 Inches Maximum
ener Length: 0.890 Inch	es Minimum And 0.937 Inches Maximum
d Style: Hexagon	
d Height: 0.109 Inch	es Minimum And 0.141 Inches Maximum
h Between Flats: 0.365 Inch	es Minimum And 0.377 Inches Maximum
Diameter: 0.3737 Inc	nes Minimum And 0.3742 Inches Maximum
inal Thread Diameter: 0.190 Inch	25
Length: 2.922 Inch	es Minimum And 2.954 Inches Maximum
ad Quantity Per Inch: 32	
mum Tensile Strength: 125000 Po	unds Per Square Inch
Iness Rating: 26.0 Rockv	ell C Minimum Overall And 32.0 Rockwell C Maximum Overall
ace Finish: 63.0 Microi	nches Bearing Surface Of Head
ace Finish: 63.0 Microi	nches Grip
Steel Comp	431 Overall
erial Document And Classification: Mil-s-18732	2 Mil Spec Single Material Response Overall
ace Treatment: Passivate 0	Overall

How to Order

Order this close tolerance bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/AN173C7A</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.