

## Description

Fastener Length: 1-1/16", Thread: 10-32, Thread Length: 29/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	AN173DD10
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-165-8615
National Motor Freight:	013280, Alum Bolts



# P/N AN173DD10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.374 Inches Minimum And 0.453 Inches Maximum
Fastener Length:	1.015 Inches Minimum And 1.062 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Grip Diameter:	0.1889 Inches Minimum And 0.1894 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Nominal First Hole
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.609 Inches Minimum And 0.641 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.875 Inches Minimum First Hole And 0.907 Inches Maximum First Hole
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Aluminum Alloy 6061 Overall Or Aluminum Alloy 2024 Overall Or Aluminum Alloy Overall
Surface Treatment:	Oxide Film Overall Or Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Overall Or Mil-a-8625 Mil Spec 2nd Treatment Response Overall
Thread Series Designator:	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN173DD10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.