

P/N AN174-12

Military-Fasteners.com

Description

Length: 1-9/32", Grip: 13/16", Thread: 1/4-28, cadmium plated steel, drilled shank, AN174 series bolt

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AN17412
Minimum Qty (MOQ):	25
NSN:	5306-00-145-7659
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN174-12 Specifications

Thread Direction: Right-hand Thread Length: 0.437 Inches Minimum And 0.516 Inches Maximum Fastener Length: 1.265 Inches Minimum And 0.312 Inches Maximum Head Style: Hexagon Head Height: 0.140 Inches Minimum And 0.172 Inches Maximum Head Height: 0.428 Inches Minimum And 0.051 Inches Maximum Hole Diameter: 0.468 Inches Minimum And 0.051 Inches Maximum Hole Diameter: 0.468 Inches Minimum And 0.058 Inches Maximum Grip Diameter: 0.2497 Inches Minimum And 0.058 Inches Maximum First Hole Nominal Thread Diameter: 0.076 Inches Minimum And 0.028 Inches Maximum First Hole Nominal Thread Diameter: 0.076 Inches Minimum And 0.028 Inches Maximum First Hole Nominal Thread Diameter: 0.076 Inches Minimum And 0.028 Inches Maximum First Hole Nominal Thread Diameter: 0.076 Inches Minimum And 0.028 Inches Maximum First Hole Nominal Thread Diameter: 0.076 Inches Maximum And 0.081 Inches Maximum Hole Quantity: 1 Hole Congrity: 1 Hole Congrity: 1280 Congrity: Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Onsteel Comp 430.0 Noreall Onsteel Comp 430.0 Noreall Onsteel Comp 430.	Thread Class:	За
Thread Length:0.437 Inches Minimum And 0.516 Inches MaximumFaster Length:1.265 Inches Minimum And 1.312 Inches MaximumHead Height:0.160 Inches Minimum And 0.172 Inches MaximumHead Height:0.410 Inches Minimum And 0.172 Inches MaximumWidth Between Flats:0.428 Inches Minimum And 0.056 Inches MaximumHole Diameter:0.046 Inches Minimum And 0.056 Inches MaximumOrd Diameter:0.046 Inches Minimum And 0.2492 Inches MaximumOrd Diameter:0.056 Inches Minimum And 0.2492 Inches Maximum First HoleNominal Thread Diameter:0.050 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.796 Inches Minimum And 0.828 Inches MaximumHole Quantity:0.796 Inches Minimum And 0.828 Inches MaximumHole Quantity:0.796 Inches Minimum And 0.828 Inches MaximumHole Type:DilledHole Type:DilledHole Strength:1.5000 Pounds Per Square InchHole Configuration Style:Neagon FlatsBurdace From Head Largest Bearing Surface Of3.124 Inches Nominal First HoleStrake Frinshi:6.30 Microinches Garing Surface Of HeadSurface Finish:6.30 Microinches Garing Surface Of HeadMaterial:Siele Comp 4140 Overall Or Steel Comp 8400 Orsteel Comp 850 Overall Orsteel Comp 8130 Overall Orsteel Comp 8130 OverallSurface Frinshi:Siele Comp 4140 Overall Or Steel Comp 8400 Orsteel Comp 830 Overall Orsteel Comp 8130 Overall Ors	Thread Direction:	
Pastener Length:1.265 Inches Minimum And 1.312 Inches MaximumHead Style:Hexa qonHead Height:0.140 Inches Minimum And 0.172 Inches MaximumHead Height:0.428 Inches Minimum And 0.420 Inches MaximumHole Diameter:0.046 Inches Minimum And 0.2492 Inches MaximumBrip Diameter:0.2487 Inches Minimum And 0.2492 Inches MaximumShank Unthreaded Hole Diameter:0.250 Inches Minimum First Hole And 0.056 Inches MaximumSoninal Thread Diameter:0.250 Inches Minimum And 0.2492 Inches Maximum First HoleGrip Length:0.796 Inches Minimum And 0.2492 Inches MaximumHole Quantity:1Hole Quantity:1Hole Quantity:1Hole Quantity:1Brance Reingth:12500 Pounds Per Square InchHole Congrigation Style:Hexagon FlatsBrance From Head Largest Bearing Surface1241 Inches Namial First HoleShark Kole Center:0.30 Microinches Bearing Surface Of HeadSurface Finish:6.30 Microinches Grap Und Overall Or Steel Comp 8740 Overall Or Steel Comp 8730 Overall Or Steel Comp 8730 OverallSurface Finish:Steel Comp 4140 Or Steel Comp 8740 Overall Or Steel Comp 8730 Overall Overall Or Steel Comp 8740 Overall Or Steel Comp 8730 Overall Overall Overall OverallSurface Treatment:Cadmiun And Consati CoverallSurface Treatment:Cadmiun And Consati CoverallSurface Treatment:Cadmiun And CoverallSurface Treatment:Cadmiun Verrall And Chromate OverallSurface Finish:Cadmiun Verrall And Chromate OverallSurface Treatment:Cadmiun And C	Thread Length:	
Head Style:HexagonHead Height:0.140 Inches Minimur And 0.172 Inches MaximumWidth Between Flats:0.428 Inches Minimur And 0.440 Inches MaximumHole Diameter:0.428 Inches Minimur And 0.056 Inches MaximumStank Unthreaded Hole Diameter:0.428 Inches Minimur And 0.2492 Inches Maximum First HoleNomial Thread Diameter:0.250 Inches Minimur And 0.2492 Inches Maximum First HoleNomial Thread Diameter:0.250 Inches Minimur And 0.2492 Inches Maximum First HoleNomial Thread Diameter:0.250 Inches Minimur And 0.828 Inches Maximum First HoleNomial Thread Diameter:0.250 Inches Minimur And 0.828 Inches Maximum First HoleHole Quartity:1Hole Quartity:1Binimur Tensile Strength:0.500 Pounds Per Square InchHardness Rating:0.600 Roukel C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsStrace From Head Largest Bearing Surface The0.30 Microinches Bearing Surface Of HeadSurface Finish:6.30 Microinches Gearing Surface Of HeadMaterial:Scol Comp 4140 Overall Or Steel Comp 8430 Overall Or Steel Comp 84	-	1.265 Inches Minimum And 1.312 Inches Maximum
Head Height:0.400 Inches Minimum And 0.172 Inches MaximumWidth Between Flats:0.428 Inches Minimum And 0.440 Inches MaximumHole Diameter:0.046 Inches Minimum And 0.055 Inches MaximumGrip Diameter:0.2487 Inches Minimum And 0.2492 Inches Maximum First HoleShank Unthreaded Hole Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleGrip Length:0.796 Inches Minimum And 0.828 Inches Maximum First HoleHole Quantity:0.796 Inches Minimum And 0.828 Inches MaximumHole Quantity:0.796 Inches Maximum And 0.828 Inches MaximumHole Quantity:0.796 Inches Main Maximum And 0.828 Inches MaximumHole Quantity:0.796 Inches Maximum And 0.828 Inches MaximumHole Quantity:0.796 Inches Maximum And 0.828 Inches MaximumHole Quantity:0.796 Inches Gaunti And Oncole StatuHole Quantity:0.796 Inches Gaunti And Chomate OrealHore Configuration Style:0.796 Inches Gaunti Statu Gaunti And Chomate OveralStatu E Constatu And Chomate Overal<	-	Hexagon
Width Between Flats:0.428 Inches Minimum And 0.440 Inches MaximumHole Diameter:0.046 Inches Minimum And 0.056 Inches MaximumGrip Diameter:0.2487 Inches Minimum And 0.2492 Inches Maximum First HoleShank Unthreadel Hole Diameter:0.260 InchesSominal Thread Diameter:0.250 InchesGrip Length:0.796 Inches Minimum And 0.828 Inches Maximum First HoleHole Quantity:0.796 Inches Minimu And 0.828 Inches MaximumHole Quantity:0.796 Inches Minimum And 0.828 Inches MaximumHole Quantity:0.796 Inches Minimu And 0.828 Inches MaximumHole Quantity:0.796 Inches Minimu And 0.828 Inches MaximumHole Quantity:0.796 Inches Minimu And 0.828 Inches MaximumHole Quantity:0.796 Inches Maximum And 0.828 Inches MaximumHole Quantity:1.400 Inches Maximum And 0.828 Inches Maximum And 0.828 Inches MaximumHole Quantity:1.800 Pounds Per Square InchHardness Rating:2.600 Pounds Per Square InchHole Configuration Style:1.241 Inches Nominal First HoleHole Configuration Style:3.01 Microinches GripSurface Finish:6.30 Microinches GripMaterial:Cel Comp 4140 Overall Or Steel Comp 870 Overall Or Steel Comp 873 OverallMaterial:Seel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8730 Or Steel Comp 873 Or Steel Comp 4130 Or Steel Comp 4037 OverallMaterial:Garimu Ov	-	
Grip Diameter:0.2487 Inches Minimum And 0.2492 Inches MaximumShank Unthreaded Hole Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.250 InchesGrip Length:0.796 Inches Minimum And 0.228 Inches MaximumHole Quantity:1Hole Quantity:1Hole Type:DrilledThread Quantity Per Inch:28Brinimum Tensile Strength:125000 Pounds Per Square InchHole Configuration Style:Hexagon FlatsDistance From Head Largest Bearing Surface The124 Inches Nominal First HoleSurface Finish:63.0 Microinches Bearing Surface Of HeadSurface Finish:63.0 Microinches Grip Surface Of HeadSurface Finish:51.0000 Jurceil Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 8730 Overall Or Steel Com		0.428 Inches Minimum And 0.440 Inches Maximum
Shank Unthreade Hole Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.250 InchesGrip Length:0.796 Inches Minimum And 0.828 Inches MaximumHole Quantity:1Hole Quantity:0.760 Inches Minimum And 0.828 Inches MaximumHole Quantity:0.760 Inches Minimum And 0.828 Inches MaximumHole Quantity:0.760 Inches Minimum And 0.828 Inches MaximumHole Quantity Per Inch:0.760 Inches Maximum OrealBardenses Rating:0.600 Pounds Per Square InchHardness Rating:6.00 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsDistance From Head Largest Bearing Surface To Shank Hole Center:0.30 Microinches Bearing Surface Of HeadSurface Finish:6.3.0 Microinches GripMaterial:Sel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8730 Overall Or Steel Comp 8730 OverallMaterial:Steel Comp 4140 Overall Or Steel Comp 8630 Or Steel Comp 8735 Overall Or Steel CompSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-16 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Hole Diameter:	0.046 Inches Minimum And 0.056 Inches Maximum
Shank Unthreade Hole Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.250 InchesGrip Length:0.796 Inches Minimum And 0.828 Inches MaximumHole Quantity:1Hole Quantity:0.760 Inches Minimum And 0.828 Inches MaximumHole Quantity:0.760 Inches Minimum And 0.828 Inches MaximumHole Quantity:0.760 Inches Minimum And 0.828 Inches MaximumHole Quantity Per Inch:0.760 Inches Maximum OrealBardenses Rating:0.600 Pounds Per Square InchHardness Rating:6.00 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsDistance From Head Largest Bearing Surface To Shank Hole Center:0.30 Microinches Bearing Surface Of HeadSurface Finish:6.3.0 Microinches GripMaterial:Sel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8730 Overall Or Steel Comp 8730 OverallMaterial:Steel Comp 4140 Overall Or Steel Comp 8630 Or Steel Comp 8735 Overall Or Steel CompSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-16 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Grip Diameter:	0.2487 Inches Minimum And 0.2492 Inches Maximum
Grip Length:0.796 Inches Minimum And 0.828 Inches MaximumHole Quantity:1Hole Type:DrilledThread Quantity Per Inch:28Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsDistance From Head Largest Bearing Surface D3.0 Microinches Bearing Surface O HeadSurface Finish:63.0 Microinches Bearing Surface Of HeadSurface Finish:63.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallSurface Treatment:Codmium Overall And Chromate OverallSurface Treatment:Cadmium And Chromate OverallSurface Treatment Document And Classification:Q-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall	-	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Hole Quantity:1Hole Type:DrilledThread Quantity Per Inch:28Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsDistance From Head Largest Bearing Surface To Shank Hole Center:1.124 Inches Nominal First HoleSurface Finish:63.0 Microinches Bearing Surface Of HeadSurface Finish:63.0 Microinches Bearing Surface Of HeadMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8730 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classificatio:Q-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.250 Inches
Hole Type:DrilledThread Quantity Per Inch:28Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsDistance From Head Largest Bearing Surface To Shank Hole Center:1.124 Inches Nominal First HoleSurface Finish:63.0 Microinches Bearing Surface Of HeadSurface Finish:63.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium And Chromate OverallSurface Treatment And Classification:0q-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Grip Length:	0.796 Inches Minimum And 0.828 Inches Maximum
Arread Quantity Per Inch:28Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsDistance From Head Largest Bearing Surface To Shank Hole Center:1.124 Inches Nominal First HoleSurface Finish:63.0 Microinches Bearing Surface Of HeadSurface Finish:63.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium And Chromate OverallSurface Treatment Document And ClassificationQ-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Hole Quantity:	1
Minim Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsDistance From Head Largest Bearing Surface To Shank Hole Center:3.124 Inches Nominal First HoleSurface Finish:63.0 Microinches Bearing Surface Of HeadSurface Finish:63.0 Microinches GripMaterial:Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 OverallMaterial:Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium And Chromate OverallSurface Treatment Document And Classification:Q-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Hole Type:	Drilled
Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon FlatsDistance From Head Largest Bearing Surface To Shank Hole Center:1.124 Inches Nominal First HoleSurface Finish:63.0 Microinches Bearing Surface Of HeadSurface Finish:63.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 OverallMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium And Chromate OverallSurface Treatment Document And Classification:Qu-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	28
Hole Configuration Style:Hexagon FlatsDistance From Head Largest Bearing Surface To Shank Hole Center:1.124 Inches Nominal First HoleSurface Finish:63.0 Microinches Bearing Surface Of HeadSurface Finish:63.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 OverallMaterial:Steel Comp 4140 Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qu-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:1.124 Inches Nominal First HoleSurface Finish:63.0 Microinches Bearing Surface Of HeadSurface Finish:63.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial:Steel Comp 4140 Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 4037 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium And Chromate OverallSurface Treatment Document And Classification:Qr.p-161 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Shank Hole Center:1.124 Inches Nominal First HoleSurface Finish:63.0 Microinches Bearing Surface Of HeadSurface Finish:63.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 4735 Overall Or Steel Comp 4037 OverallMaterial:Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 4130 Or Steel Comp 4037 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Hole Configuration Style:	Hexagon Flats
Surface Finish:63.0 Microinches GripMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 OverallMaterial:Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 4130 Or Steel Comp 4037 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium And Chromate OverallSurface Treatment:Cadmium And Chromate OverallOperation:O		1.124 Inches Nominal First Hole
Material:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial:Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 8740 Or Steel Comp 8740 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel CompSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium And Chromate OverallSurface Treatment:Opp-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Surface Finish:	63.0 Microinches Bearing Surface Of Head
Material:Comp 4130 Overall Or Steel Comp 4037 OverallMaterial:Steel Comp 4140 Or Steel Comp 8740 Or Steel Comp 8630 Or Steel Comp 8735 Or Steel Comp 4130 Or Steel Comp 4037 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium And Chromate OverallSurface Treatment:Oq-P-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Surface Finish:	63.0 Microinches Grip
Material:4037 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Material:	
Surface Treatment: Cadmium And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Material:	
Surface Treatment Document And Classification: Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment:	Cadmium And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unf

How to Order

Order this close tolerance bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/AN174-12</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.