

**Description**

length: 1-9/32", grip: 13/16", thread: 1/4-28, cadmium plated steel undrilled shank"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN17412A
Minimum Qty (MOQ):	10
NSN:	5306-00-151-2592
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN174-12A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.469 Inches Minimum
<b>Fastener Length:</b>	1.265 Inches Minimum And 1.312 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.156 Inches Nominal
<b>Width Between Flats:</b>	0.428 Inches Minimum And 0.440 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.812 Inches Nominal
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Dichromate Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN174-12A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.