

Description

length: 1-9/32", grip: 13/16", thread: 1/4-28, cadmium plated steel undrilled shank"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN17412A
Minimum Qty (MOQ):	10
NSN:	5306-00-151-2592
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN174-12A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Minimum
Fastener Length:	1.265 Inches Minimum And 1.312 Inches Maximum
Head Style:	Hexagon
Head Height:	0.156 Inches Nominal
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.812 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Dichromate Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN174-12A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.