

P/N AN174-13

Description

length: 1-13/32", grip: 15/16", thread: 1/4-28, cadmium plated steel, drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN17413

Minimum Qty (MOQ): 20

NSN: 5306-00-855-3610

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN174-13 Specifications

Thread Direction: Right-hand Thread Length: 0.438 Inches Minimum And 0.516 Inches Maximum Fastener Length: 1.391 Inches Minimum And 1.438 Inches Maximum Head Style: Hexagon Head Height: 0.140 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Shank Unthreaded Hole Dlameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Onominal Thread Diameter: 0.250 Inches Grip Length: 0.922 Inches Minimum And 0.953 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 25eel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Material Document And Mini-Sco26 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or		
Thread Length: 0.438 Inches Minimum And 0.516 Inches Maximum Fastener Length: 1.391 Inches Minimum And 0.438 Inches Maximum Head Style: Head Height: 0.140 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Shank Unthreaded Hole Diameter: 0.766 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 0.922 Inches Minimum And 0.953 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 0.540 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material: Material Document And Classification: Will-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-675	Thread Class:	3a
Fastener Length: 1.391 Inches Minimum And 1.438 Inches Maximum Head Style: Hexagon Head Height: 0.428 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 0.922 Inches Minimum And 0.953 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Material: Steel Comp 4037 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Mil-s-6029 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6078 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mins 6300	Thread Direction:	Right-hand
Head Style: Hexagon Head Height: 0.140 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 0.922 Inches Minimum And 0.953 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Document And Classification: Q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Thread Length:	0.438 Inches Minimum And 0.516 Inches Maximum
Head Height: 0.140 Inches Minimum And 0.172 Inches Maximum Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 0.922 Inches Minimum And 0.953 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center Inches Minim	Fastener Length:	1.391 Inches Minimum And 1.438 Inches Maximum
Width Between Flats: 0.428 Inches Minimum And 0.440 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 0.922 Inches Minimum And 0.953 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole 20 Center: 2540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: 3540 Inches Minimum First Hole And 1.260 Inches Maximum F	Head Style:	Hexagon
Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 0.922 Inches Minimum And 0.953 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Nominal Thread Diameter: 0.250 Inches Grip Length: 0.922 Inches Minimum And 0.953 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Bocument And Classification: Material Response Overall Or Mil-s-6058 Mil Spec 2th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758	Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Grip Length: 0.922 Inches Minimum And 0.953 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Steel Comp 4040 Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 3th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 3th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 3th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 3th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 3th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 3th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 3th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 3th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 3th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 3th Material R	Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Features Provided: Finished Head Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Oq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch: 28 Minimum Tensile Strength: 125000 Pounds Per Square Inch 125000 Pounds Pounds Inch 125000 Pounds Per Square Inch 125000 Pounds Per Square Inch 125000 Pounds Per Square Inch 12500 Pounds Per Square I	Grip Length:	0.922 Inches Minimum And 0.953 Inches Maximum
Minimum Tensile Strength: 125000 Pounds Per Square Inch 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mili-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mis 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Features Provided:	Finished Head
Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Center: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	28
Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole Comp 4120 Inches Maximum First Hole 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole 1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole 1.240 Inches Minimum First Hole 1.240 Inches Maximum First Hole 1.240 Inches Minimum First Hole 1.240 Inches Maximum First Hole 1.240 Inches Minimum First Hole 1.240 Inches Maximum First Hole 1.240 Inches Minimum First Hole 1.240 Inches Minimum First Hole 1.240 Inches Maximum First Hole 1.240 Inches M	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Surface Treatment Document And Classification: Surface Treatment Document And Classification: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification:	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material: Material Document And Classification: Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Distance From Head Largest Bearing Surface To Shank Hole Center:	1.240 Inches Minimum First Hole And 1.260 Inches Maximum First Hole
Material Document And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Material:	
Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Material Document And Classification:	Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or
Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
-	Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN174-13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/AN174-13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/AN174-13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/AN174-13 and selecting the quantity you want then