



★ FASTENERS

Military-Fasteners.com

P/N AN174-24A

Description

length: 2-17/32", grip: 2-1/16", thread: 1/4-28, cadmium plated steel, undrilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN17424A |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5306-00-180-2758 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N AN174-24A Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Length: | 0.469 Inches Minimum |
| Fastener Length: | 2.531 Inches Nominal |
| Head Height: | 0.140 Inches Minimum And 0.172 Inches Maximum |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 63.0 Microinches Bearing Surface Of Head |
| Material: | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN174-24A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.