

## **P/N AN174-33**

## **Description**

length: 3-13/32", grip: 2-15/16", thread: 1/4-28, cadmium plated steel, drilled shank, AN174 series bolt

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN17433

Minimum Qty (MOQ):

NSN: 5306-00-180-0453

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N AN174-33 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.437 Inches Minimum And 0.516 Inches Maximum
Fastener Length:	3.390 Inches Minimum And 3.437 Inches Maximum
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Grip Diameter:	0.2487 Inches Minimum And 0.2492 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.921 Inches Minimum And 2.953 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	3.233 Inches Minimum First Hole And 3.265 Inches Maximum First Hole
Surface Finish:	63.0 Microinches Grip
Material:	Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

## **How to Order**

Order this close tolerance bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/AN174-33">https://military-fasteners.com/bolts/close+tolerance+bolts/AN174-33</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.