



★ FASTENERS

Military-Fasteners.com

P/N AN174-7A

Description

Length: 29/32", grip: 7/16", thread: 1/4-28, cadmium plated steel undrilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN1747A
Minimum Qty (MOQ):	25
NSN:	5306-00-206-5748
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN174-7A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.468 Inches Minimum
Fastener Length:	0.906 Inches Nominal
Head Style:	Hexagon
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Grip Diameter:	0.2487 Inches Minimum And 0.2492 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.438 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN174-7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.