

P/N AN175-12

Description

length: 1-11/32", grip: 13/16", thread: 5/16-24, cadmium plated steel drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN17512
Minimum Qty (MOQ):	4
NSN:	5306-00-639-2458
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN175-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Minimum And 0.579 Inches Maximum
Fastener Length:	1.328 Inches Minimum And 1.375 Inches Maximum
Head Style:	Hexagon
Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Grip Diameter:	0.3112 Inches Minimum And 0.3117 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.796 Inches Minimum And 0.828 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.171 Inches Nominal First Hole
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/AN175-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/AN175-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/AN175-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/AN175-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/AN175-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/AN175-12 and selecting the your cart you can check out https://military-fasteners.com/bolts/AN175-12 and selecting the your cart you can check out https://military-fasteners.com/bolts/AN175-12 and selecting the your cart you can check out https://military-fasteners.com/bolts/AN175-12 and selecting the your cart your cart you can check you can check