

# P/N AN175-14

Military-Fasteners.com

#### Description

length: 1-19/32", grip: 1-1/16", thread: 5/16-24, cadmium plated steel, drilled shank, AN175 series bolt

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | AN17514                                   |
|-------------------------|---|
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5306-00-180-0469                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N AN175-14 Specifications

| Thread Class:  | 3a   |
|--|--|
| Thread Direction:  | Right-hand   |
| Thread Length:   | 0.500 Inches Minimum And 0.579 Inches Maximum  |
| Fastener Length:   | 1.579 Inches Minimum And 1.625 Inches Maximum  |
| Head Style:  | Hexagon  |
| Head Height:   | 0.172 Inches Minimum And 0.204 Inches Maximum  |
| Width Between Flats:   | 0.490 Inches Minimum And 0.502 Inches Maximum  |
| Grip Diameter:   | 0.3112 Inches Minimum And 0.3117 Inches Maximum  |
| Shank Unthreaded Hole Diameter:  | 0.076 Inches Nominal First Hole  |
| Nominal Thread Diameter:   | 0.312 Inches   |
| Grip Length:   | 1.062 Inches Nominal   |
| Thread Quantity Per Inch:  | 24   |
| Minimum Tensile Strength:  | 125000 Pounds Per Square Inch  |
| Hardness Rating:   | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |
| Distance From Head Largest<br>Bearing Surface To Shank Hole<br>Center: | 1.421 Inches Nominal First Hole  |
| Surface Finish:  | 63.0 Microinches Bearing Surface Of Head   |
| Surface Finish:  | 63.0 Microinches Grip  |
| Material:  | Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140<br>Overall Or Steel Comp 4130 Overall  |
| Material Document And<br>Classification:                               | Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd<br>Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or<br>Mil-s-6758 Mil Spec 6th Material Response Overall |
| Surface Treatment:   | Cadmium Overall And Chromate Overall   |
| Surface Treatment Document And<br>Classification:                      | Qq-p-416 Type 2 Class 3 Fed Spec All Treatment Responses Overall   |
| Thread Series Designator:  | Unf  |
|  |  |

### How to Order

Order this close tolerance bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/close+tolerance+bolts/AN175-14</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.