

**Description**

length: 2-11/32", grip: 1-13/16", thread: 5/16-24, cadmium plated steel drilled shank

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN17522
Minimum Qty (MOQ):	5
NSN:	5306-00-180-0474
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN175-22 Specifications

<b>Thread Class:</b>	3a
<b>Thread Length:</b>	0.532 Inches Minimum
<b>Fastener Length:</b>	2.344 Inches Nominal
<b>Head Height:</b>	0.172 Inches Minimum And 0.204 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Nominal First Hole
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall
<b>Material Document And Classification:</b>	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN175-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.