

Description

length: 2-11/32", grip: 1-13/16", thread: 5/16-24, cadmium plated steel drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN17522
Minimum Qty (MOQ):	5
NSN:	5306-00-180-0474
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN175-22 Specifications

Thread Class:	3a
Thread Length:	0.532 Inches Minimum
Fastener Length:	2.344 Inches Nominal
Head Height:	0.172 Inches Minimum And 0.204 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Material:	Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN175-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.