

Description

Fastener Length: 1-11/32", Thread: 1/4-24, Thread Length: 1/2", AN175 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | AN175C12 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-301-3754 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |



P/N AN175C12 Specifications

| | |
|-------------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.529 Inches Nominal |
| Fastener Length: | 1.326 Inches Minimum And 1.356 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.172 Inches Minimum And 0.204 Inches Maximum |
| Width Between Flats: | 0.580 Inches Nominal |
| Grip Diameter: | 0.3112 Inches Minimum And 0.3117 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.797 Inches Minimum And 0.827 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Material: | Steel Corrosion Resisting Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 88044-an175 Government Standard |

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN175C12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.