

Description

length: 2-21/64", grip: 1-11/16", thread: 3/8-24, cadmium plated steel drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN17622
Minimum Qty (MOQ):	2
NSN:	5306-00-051-6874
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN176-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.641 Inches Minimum
Fastener Length:	2.328 Inches Nominal
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Grip Diameter:	0.3742 Inches Minimum And 0.3787 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.687 Inches Nominal
Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.124 Inches Nominal First Hole
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Steel Overall
Thread Series Designator:	Unf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN176-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.