

## **P/N AN176-37A**

### **Description**

Fastener Length: 3-63/64", Thread: 3/8-24, Thread Length: 11/16", AN176 series bolt

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN17637A

Minimum Qty (MOQ): 5

NSN: 5306-00-584-7499

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN176-37A Specifications

| Thread Class:                                  | 3a   |
|--|--|
| Thread Direction:                              | Right-hand   |
| Thread Length:                                 | 0.609 Inches Minimum And 0.688 Inches Maximum  |
| Fastener Length:                               | 3.937 Inches Minimum And 3.984 Inches Maximum  |
| Head Style:                                    | Hexagon  |
| Head Height:                                   | 0.203 Inches Minimum And 0.235 Inches Maximum  |
| Width Between Flats:                           | 0.553 Inches Minimum And 0.565 Inches Maximum  |
| Grip Diameter:                                 | 0.3737 Inches Minimum And 0.3742 Inches Maximum  |
| Nominal Thread Diameter:                       | 0.375 Inches   |
| Grip Length:                                   | 3.296 Inches Minimum And 3.328 Inches Maximum  |
| Thread Quantity Per Inch:                      | 24   |
| Minimum Tensile Strength:                      | 125000 Pounds Per Square Inch  |
| Hardness Rating:                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |
| Material:                                      | Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall |
| Material Document And Classification:          | Mil-b-6812 Mil Spec All Material Responses Overall   |
| Surface Treatment:                             | Cadmium Overall And Chromate Overall   |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall  |
| Thread Series Designator:                      | Unf  |

## **How to Order**

Order this close tolerance bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/AN176-37A">https://military-fasteners.com/bolts/close+tolerance+bolts/AN176-37A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/AN176-37A">https://military-fasteners.com/bolts/close+tolerance+bolts/AN176-37A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/AN176-37A">https://military-fasteners.com/bolts/close+tolerance+bolts/AN176-37A</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/AN176-37A">https://military-fasteners.com/bolts/close+tolerance+bolts/AN176-37A</a> and selecting the quantity you want then click "add to cart".